

DIAMETERS				Part Number		Dimensions (Inches)	Wt. (Lbs.) Less Bush.
Datum "A" Belts	Datum "B" Belts	Pitch "5V" Belts	Outside	Sheave	Bushing	OL	
<b>3 Grooves, Face Width = 2 7/16</b>							
3.8	4.2	4.3	4.48	385V42	P1	3 5/16	4.8
4.0	4.4	4.5	4.68	385V44	P1	2 23/32	5.2
4.2	4.6	4.7	4.88	385V46	B	3 7/16	4.9
4.4	4.8	4.9	5.08	385V48	B	3 7/16	5.5
4.6	5.0	5.1	5.28	385V50	B	3 7/16	6.1
4.8	5.2	5.3	5.48	385V52	B	3 7/16	6.7
5.0	5.4	5.5	5.68	385V54	B	2 27/32	7.4
5.2	5.6	5.7	5.88	385V56	B	2 27/32	8.4
5.4	5.8	5.9	6.08	385V58	B	2 27/32	9.5
5.6	6.0	6.1	6.28	385V60	B	2 27/32	10.6
5.8	6.2	6.3	6.48	385V62	B	2 27/32	9.8
6.0	6.4	6.5	6.68	385V64	B	2 27/32	10.5
6.2	6.6	6.7	6.88	385V66	B	2 27/32	10.4
6.4	6.8	6.9	7.08	385V68	B	2 27/32	10.9
6.6	7.0	7.1	7.28	385V70	B	2 27/32	11.5
7.0	7.4	7.5	7.68	385V74	B	2 27/32	12.6
7.6	8.0	8.1	8.28	385V80	B	2 27/32	14.2
8.2	8.6	8.7	8.88	385V86	B	2 27/32	13.7
8.6	9.0	9.1	9.28	385V90	B	2 27/32	14.5
9.0	9.4	9.5	9.68	385V94	B	2 27/32	17.0
10.6	11.0	11.1	11.28	385V110	B	2 27/32	19.8
12.0	12.4	12.5	12.68	385V124	B	2 27/32	22.1
13.2	13.6	13.7	13.88	385V136	B	2 27/32	24.9
15.0	15.4	15.5	15.68	385V154	B	2 27/32	30.4
15.6	16.0	16.1	16.28	385V160	B	2 27/32	31.7
18.0	18.4	18.5	18.68	385V184	B	2 27/32	40.9
19.5	20.0	20.1	20.28	385V200	B	2 27/32	47.6
22.9	23.4	23.5	23.68	385V234	B	2 27/32	61.5
24.5	25.0	25.1	25.28	385V250	B	2 27/32	66.6
27.3	27.8	27.9	28.08	385V270	B	2 27/32	79.1



**Browning B5V...The most significant advance in belt drives since the V-groove!** With the introduction of the revolutionary B5V line, Browning brings up-to-the-minute technology to drive design, operation and inventory control. Now - more than ever - when you specify Browning, you select from the most extensive V-belt drive line in the world.

- **Combination groove B5V Sheaves** - with 170 plus components covering 10-125 hp range. Mix and match with conventional A, B and 5V components.