



Coupling Number	Maximum Bore Inches	Minimum Plain Bore Inches	Weight (lb)	Recommended Maximum RPM	Coupling Chain Number	Weight (lb)
4012	.875	.438	.5	5000	4012 CHN	.4
4016	1.313	.625	1.0	5000	4016 CHN	.5
5016	1.688	.625	2.2	4000	5016 CHN	1.2
5018	2	.75	3.5	3600	5018 CHN	1.3
6018	2.438	1	5.0	3000	6018 CHN	2.2
6020	2.75	1.125	6.5	2500	6020 CHN	2.6
6022	3	1.125	9.4	2500	6022 CHN	2.7
8018	3.125	1.125	11.0	2000	8018 CHN	5.3
8020	3.563	1.5	16.3	2000	8020 CHN	5.9
10018	3.875	1.5	20.3	1800	10018 CHN	9.8
10020	4.625	1.5	31.8	1800	10020 CHN	10.9
12018	4.688	2	36.8	1500	12018 CHN	17.3
12022	6.125	2	70.0	1200	12022 CHN	21.2

Coupling Number	Stock Finished Bores Include Standard Keyway and Setscrew				Coupling O.D.	Weight (lb)	
	A	B	C	L			
4012	.5, .625, .75	1.406	1.125	.281	2.531	2.406	.4
4016	.625, .75, .875, .938, 1, 1.125, 1.188, 1.25	1.969	1.125	.281	2.531	3.031	.8
5016	.75, .875, 1, 1.125, 1.188, 1.25, 1.375, 1.438, 1.5, 1.625	2.5	1.438	.375	3.25	3.781	1.6
5018	.75, .875, 1, 1.125, 1.188, 1.25, 1.375, 1.438, 1.5, 1.625, 1.75, 1.875, 1.938	2.969	1.688	.375	3.75	4.188	2.4
6018	1, 1.125, 1.188, 1.25, 1.375, 1.438, 1.5, 1.625, 1.75, 1.875, 1.938, 2, 2.125, 2.188, 2.25, 2.375, 2.438	3.5	1.875	.438	4.188	5	4.8
6020	1.125, 1.25, 1.5, 1.75, 1.938, 2.125, 2.375, 2.438, 2.625	3.875	2	.438	4.438	5.5	5.2
6022	1.125, 1.75, 1.875, 1.938, 2.125, 2.375, 2.438, 2.625, 2.75, 2.875	4.5	2.125	.438	4.688	5.953	7.8
8018	1.125, 1.75, 1.938, 2, 2.125, 2.375, 2.438, 2.625, 2.875, 2.938	4.563	2.375	.578	5.328	6.656	9.5
8020	1.5, 2.188, 2.438, 2.688, 2.938, 3.125, 3.375, 3.438	5.375	2.625	.578	5.516	7.297	13.4
10018	1.5, 2.438, 2.875, 2.938, 3.438	5.688	2.75	.719	6.219	8.328	18.2
10020	2, 3.375, 3.688, 3.938	6.719	3.125	.719	6.969	9.125	25.0
12018	3.438, 3.938, 4.438	6.75	3.5	.859	7.875	10	28.0
12022	4.375, 4.438, 4.938	8.75	4	.859	8.875	11.891	55.0