

**Lovejoy**  
®

BY TIMKEN

SFE

# S-Flex Endurance

## IN THIS SECTION:

- J Type Couplings
- S Type Couplings
- B Type Couplings
- SC Type Spacers
- T Type Couplings



# Warnings

 **WARNING**

*Failure to observe the following warnings could cause the power transmission product to break and parts to be thrown with sufficient force to cause serious injury or death.*

**Selection.** Do not exceed catalog ratings. Refer to the Lovejoy catalog for proper selection, sizing, horsepower, torque range, and speed range of these products.

**Installation.** Proper maintenance, handling, and shop practices are critical. Follow all installation instructions included with the product and provided by your equipment manufacturer, and all applicable federal, state, and local regulations concerning the safe operation and maintenance of manufacturing equipment.

**Operation.** Avoid sudden shock loads during start up and operation.

Do not operate a coupling assembly with improper alignment or bolt torque or with damaged or worn elastomeric elements. Inspect the assembly for these conditions shortly after initial operation and periodically thereafter.

The coupling assembly should operate quietly and smoothly. If the coupling assembly vibrates or makes a beating sound, shut down the equipment immediately and recheck the alignment.

## Disclaimer

This catalog is provided solely to give you analysis tools and data to assist you in your product selection. Product performance is affected by many factors beyond the control of Lovejoy. Therefore, you must validate the suitability and feasibility of all product selections for your applications.

**Lovejoy does not manufacture or sell power transmission products for elevators, man lifts, or other devices that carry people. We make no representation or warranty concerning such uses disclaim all liability for harm that might result from the use of our products in those applications.**

Lovejoy products are sold subject to Lovejoy terms and conditions of sale (view at [www.lovejoy-inc.com/resources](http://www.lovejoy-inc.com/resources)), which include our limited warranty and remedy. Please consult with your Lovejoy engineer for more information and assistance.

Every reasonable effort has been made to ensure the accuracy of the information in this writing, but no liability is accepted for errors, omissions or for any other reason.

If you have any questions, contact the Lovejoy Engineering Department at 1-630-852-0500 or email [appleng@lovejoy-inc.com](mailto:appleng@lovejoy-inc.com).



# Table of Contents

	Running Page No.	Section Page No.
Features & Benefits .....	1 .....	SF-4
Elastomer Sleeves.....	2 .....	SF-5
Selection Process.....	3 .....	SF-6
Nomenclature .....	4 .....	SF-7
Application Service Factors > Selection Data .....	5 .....	SF-8
Performance Data .....	6 .....	SF-9
S Type Inch Bore / Keyway > Item Selection .....	7 .....	SF-10
Standard Sleeve, J and S Type Metric Bore / Keyway > Item Selection.....	8 .....	SF-11
J, SC, SCF and SCHS Type > Item Selection.....	9 .....	SF-12
Ratings > Performance Data .....	10 .....	SF-13
Sleeves > Dimensional Data.....	11 .....	SF-14
J Type > Dimensional Data .....	12 .....	SF-15
S Type > Dimensional Data.....	13 .....	SF-16
S Type Shallow Keyway > Dimensional Data .....	14 .....	SF-17
B Type with Bushings > Dimensional Data.....	15 .....	SF-18
T Type > Dimensional Data.....	16 .....	SF-19
SC Type > Dimensional Data .....	17 .....	SF-20
SC Type Flange > Dimensional Data .....	18 .....	SF-21
SC Type Hub > Dimensional Data.....	19 .....	SF-22
Engineering Data > Sleeve and Flexible Element > Chemical Resistance Chart .....	20 .....	SF-24

## Overview

**The reformulated S-Flex Endurance™ is the longest lasting and best performing EPDM product available in the marketplace today**

- The S-Flex Endurance coupling design is comprised of three parts: two flanges with internal teeth engage an elastomeric flexible sleeve with external teeth
- Torque is transmitted through the flanges mounted on both the driver and driven shafts via the sleeve
- Misalignment and torsional shock loads are absorbed by shear deflection in the sleeve
- The shear characteristic of the S-Flex Endurance coupling is very well suited to absorb impact loads
- Combinations of flanges and sleeves can be assembled to suit your specific application, along with thirteen sizes with torque capabilities from 60 in-lbs to 72,480 in-lbs
- Flanges are offered in five models which are made from zinc or cast iron
- Sleeves are available in EPDM rubber, Neoprene, or Hytrel® to address a wide variety of application requirements


SFE



### Features


- Easy to install, no special tools required
- Low maintenance, no lubrication required
- Standardized and interchangeable
- Double engagement for reliability

### Protection from misalignment, shock and vibration:




#### PARALLEL

Accepts up to .062 in of parallel misalignment without wear. The flexible coupling sleeve minimizes the radial loads imposed on equipment bearings, a problem commonly associated with parallel misalignment.




#### AXIAL

The S-Flex Endurance couplings can be used in applications which require a limited amount of shaft end-float without transferring thrust loads to equipment bearings. Axial movement of approximately 1/8 inch accepted.



#### ANGULAR

The flexing action of the elastomeric sleeve and the locking feature of the mating teeth allows the S-Flex Endurance coupling to effectively handle angular misalignment up to 1°.



#### TORSIONAL

Effectively dampens torsional shock and vibration to protect connected equipment. The EPDM and Neoprene sleeves have torsional wind-up flexibility of approximately 15° at their rated torque. Hytrel provides about 7° wind-up.

### S-Flex Endurance Coupling Components:

#### Flange Types:

- J Type** Zinc Die Cast and Cast Iron, Bore Range: 3/8" to 1-7/16"
- S Type** Cast Iron, Bore Range: 1/2" to 5-1/2"
- B Type** Cast Iron with bushing
- SC Type** Cast Iron Spacer
- TType** Cast Iron w/Taper-lock bushing

#### Hubs for SC Type Spacer Coupling:

- SCH Type** Powdered Metal or Cast Iron, *Standard Length*
- SCHS Type** Powdered Metal or Cast Iron, *Short Length*

#### Sleeve Types:

- |            |            |                          |
|------------|------------|--------------------------|
| <b>JE</b>  | (EPDM)     | 1-piece solid            |
| <b>JES</b> | (EPDM)     | 1-piece split            |
| <b>JN</b>  | (Neoprene) | 1-piece solid            |
| <b>JNS</b> | (Neoprene) | 1-piece split            |
| <b>E</b>   | (EPDM)     | 2-piece w/retaining ring |
| <b>N</b>   | (Neoprene) | 2-piece w/retaining ring |
| <b>H</b>   | (Hytrel)   | 1-piece                  |
| <b>HS</b>  | (Hytrel)   | 2-piece split            |



#### WARNING

**Failure to follow these cautions could create a risk of injury.**

You must refer to page SF-2 for Important Safety Instructions and Precautions for the selection and use of these products.

Failure to follow the instructions and precautions can result in severe injury or death.

## Components

### Meet The New EPDM Sleeve

Continue to enjoy the S-Flex benefits, just enjoy them at least 3X longer.

- Lasts at least 3X as long as the previous design, saving you valuable downtime opportunity costs and maintenance labor costs
- Provides at least 30% increased torque rating
- Allows for product downsize in 50% of applications creating an average cost savings of 23-33% for sleeve replacement

Extensive testing performed by our engineering department compared the new and improved EPDM S-Flex Endurance sleeve material to Lovejoy's previous design and to the competition. Ultimately, Lovejoy's new EPDM S-Flex Endurance material met or exceeded performance in every testing category.

Note: Performance improvements apply only to the EPDM sleeve type. Neoprene and Hytrel sleeve type performance is unchanged.



SFE



**S-Flex Endurance™**

#### Elastomer Sleeve Features

- Lovejoy offers flexible sleeves for S-Flex Endurance couplings in three designs: one-piece solid, one-piece split, and two-piece with retaining ring
- The one-piece split design provides solutions for applications with unique requirements where small shaft separations inhibit the installation of a one-piece solid sleeve
- Pre-molded teeth along the diameter of the sleeve engage with teeth of the coupling flanges
- No clamps or screws are needed to connect the flanges with the flexible sleeve which securely lock together under torque for smooth transmission of power
- Torque is transmitted through shear loading of the sleeve
- All three sleeve materials are highly elastic which permits the S-Flex Endurance coupling to protect connected equipment from harmful shock loading, vibration, and shaft misalignment

#### Sleeve Materials & Types


**EPDM** – Unless otherwise specified, S-Flex Endurance couplings are supplied with EPDM flexible sleeves. EPDM has good resistance to commonly used chemicals and is generally not affected by dirt or moisture. Color is black.

**NEOPRENE** – Neoprene provides very good performance characteristics for most applications and offers a very good resistance to chemical and oil conditions. Color is black with a green dot.

**HYTREL®** – Hytrel is a polyester elastomer designed for high torque and high temperature applications and offers excellent resistance to chemical and oil conditions. Color is orange.

Notes:

- See page SF-24 for sleeve chemical resistance chart.
- Hytrel is a registered trademark of E.I. DuPont Nemours & Co.



#### JE, JN, JES, JNS Sleeve Types

These sleeves feature a one-piece design molded in EPDM & Neoprene rubber. In the case of JES & JNS Types, the one-piece design is split to provide for ease of installation and removal.

#### E, N Sleeve Types

These sleeves feature a two-piece design with retaining ring. The E Type is molded in EPDM rubber and the N Type is molded in Neoprene. The two-piece design is ideal for applications where there is difficulty in separating the shafts of the driver and driven.

#### H, HS Sleeve Types

Featuring both a one-piece solid (H) and two-piece split (HS) design and are molded of Hytrel. The Hytrel material is designed to transmit power for high torque applications. Because of the design and the properties of the Hytrel molded sleeve, the H and HS sleeves should not be used as direct replacements for EPDM or Neoprene sleeves, and can only be used with S, TF, or SC flanges.

## Selection Process

### S-Flex Endurance Coupling Selection Process

The selection process for determining the proper S-Flex Endurance coupling requires using the charts shown on the following pages. There are a total of three components to be selected, two flanges and one sleeve.

#### Information necessary before a coupling can be selected:

- HP and RPM of Driver or running torque
- Shaft size of Driver and Driven equipment and corresponding keyways
- Application or equipment description
- Environmental conditions (i.e. extreme temperature, corrosive conditions, space limitations)

SFE

#### List of Charts provided for Selection:

- Chart 1 - Application Service Factors (page SF-8)
- Chart 2 - Sleeve Performance Data (page SF-9)
- Chart 3 - S-Flex Endurance Nominal Rated Torque Data (page SF-9)

#### Formulas:

$$\begin{aligned}\text{Nominal Torque} &= \frac{(\text{HP} \times 63025)}{\text{RPM}} \\ \text{Nm} &= \frac{(\text{KW} \times 9550)}{\text{RPM}}\end{aligned}$$

Design Torque = Nominal Torque x Application Service Factor

### Steps In Selecting An S-Flex Endurance Coupling

**Step 1:** Determine the Nominal Torque in in-lb of your application by using the following formula:

$$\text{Nominal Torque} = \frac{(\text{HP} \times 63025)}{\text{RPM}}$$

**Step 2:** Using the Application Service Factor Chart 1 (page SF-8) select the service factor which best corresponds to your application.

**Step 3:** Calculate the Design Torque of your application by multiplying the Nominal Torque calculated in Step 1 by the Application Service Factor determined in Step 2.

$$\text{Design Torque} = \text{Nominal Torque} \times \text{Application Service Factor}$$

**Step 4:** Using the Sleeve Performance Data Chart 2 (page SF-9) select the sleeve material which best corresponds to your application.

**Step 5:** Using the S-Flex Endurance Nominal Rated Torque Chart 3 (page SF-9) locate the appropriate sleeve material column for the sleeve selected in Step 4.

**Step 6:** Scan down this column to the first entry where the Torque Value in the column is greater than or equal to the Design Torque calculated in Step 3.

Refer to the maximum RPM value of the coupling size to ensure that the application requirements are met. If the maximum RPM value is less than the application requirement, S-Flex Endurance couplings are not recommended for the application.

**Note:** ■ If Nominal Torque is less than 1/4 of the coupling's nominal rated torque, misalignment capacities are reduced by 1/2. Once torque value is located, refer to the corresponding coupling size in the first column of the S-Flex Endurance Nominal Rated Torque Data Chart 3 (page SF-9).

**Step 7:** Compare the application driver/driven shaft sizes to the maximum bore size available on the coupling selected. If coupling max bore is not large enough for the shaft diameter, select the next largest coupling that will accommodate the driver/driven shaft diameters.

**Step 8:** Using the Item Selection tables, find the appropriate Keyway and Bore size required and locate the Lovejoy UPC number.

## Nomenclature

See side of box for  
the complete Item  
Description.

See breakdown of Item  
Description below:




A complete standard coupling unit consists of two flanges and one sleeve.

SFE


### Flanges

**Example Item Description: 13S FLNG 2-3/8 5/8 X 5/16 KW**



### Sleeves


**Example Item Description: 4JE SLEEVE**



### Spacers

A complete SC Type coupling consists of two SCH or SCHS hubs, two SC spacer flanges, and one sleeve.

**Example Item Description: 8SCH SPCR HUB 1-1/2 3/8KW**



### Application Service Factors

**Chart 1**

SFE	Service Factors			Service Factors			Service Factors				
	Electric Motor w/ Standard Torque	Electric Motor w/ High Torque	Turbines, Air & Hydraulic Motors	Electric Motor w/ Standard Torque	Electric Motor w/ High Torque	Turbines, Air & Hydraulic Motors	Electric Motor w/ Standard Torque	Electric Motor w/ High Torque	Turbines, Air & Hydraulic Motors		
<b>Agitators</b>	1.25	1.50	1.00	<b>Disc Feeder</b>	1.25	1.50	1.00	<b>Pressers</b>			
<b>Band Resaw</b> (lumber)	1.50	2.00	1.25	<b>Dough Mixer</b>	1.50	2.00	1.25	Brick, Briquette Machine	2.00	2.50	1.50
<b>Barge Haul Puller</b>	2.00	2.50	1.50	<b>Draw Bench Conveyor</b>				Notching, Paper, Punch			
<b>Barking</b> (lumber)	2.00	2.50	1.50	<b>&amp; Main Drive</b>	2.00	2.50	1.50	Printing	1.50	2.00	1.25
<b>Bar Screen</b> (sewage)	2.00	2.50	1.50	<b>Dredges</b>				<b>Pug Mill</b>	1.50	2.00	1.25
<b>Batches</b> (textile)	1.25	1.50	1.00	Cable reef, Pumps	1.50	2.00	1.25	<b>Pulp Grinder</b> (paper)	2.00	2.50	1.50
<b>Beater and Pulper</b>				Cutter head, Jig, &				<b>Pulverizers</b>			
(paper)	1.50	2.00	1.25	Screen Drives	2.00	2.50	1.50	Hammermill—Light Duty,			
<b>Bending Roll</b> (metal)	1.50	2.00	1.25	Maneuvering & Utility				Roller	1.50	2.50	1.25
<b>Bleacher</b> (paper)	1.25	1.50	1.00	Winch, Stacker	1.50	2.00	1.25	Hammermill—Heavy			
<b>Blowers</b>				<b>Dynamometer</b>	1.25	1.50	1.00	Duty Hog	2.00	2.50	1.50
Centrifugal, Vane	1.25	1.50	1.00					<b>Pumps</b>			
Lobe	1.50	2.00	1.25	<b>Dryers</b> (rotary)	1.50	2.00	1.25	Centrifugal, Axial	1.25	1.50	1.00
<b>Bottling Machinery</b>	1.25	1.50	1.00	<b>Edger</b> (lumber)	2.00	2.50	1.50	Gear, Lobe, Vane	1.50	2.00	1.25
<b>Brew Kettles</b> (distilling)	1.25	1.50	1.00	<b>Escalators</b> <sup>1</sup>	1.25	1.50	1.00	Reciprocating—Sgl. or			
<b>Bucket Elevator or</b>				<b>Extruders</b> (metal)	2.00	2.50	1.50	Dbl. Acting Cylinder	2.00	2.50	2.00
<b>Conveyor</b>	1.50	2.00	1.25	<b>Fans</b>				<b>Reel, Rewinder</b> (paper)			
<b>Calenders</b>				Centrifugal	1.25	1.50	1.00	Cable	1.50	2.00	1.25
Calender (paper)	1.50	2.00	1.25	Cooling Towers	2.00	2.50	1.50	<b>Rod Mill</b>	2.00	2.50	1.50
Calender (rubber),				Forced Draft, Large				<b>Saw Dust Conveyor</b>	1.25	1.50	1.00
Calender-super (paper)	2.00	2.50	1.50	Industrial	1.50	2.00	1.25	<b>Screens</b>			
<b>Cane Knives</b> (sugar)	1.50	2.00	1.25	<b>Feeders</b>				Air Washing, Water	1.25	1.50	1.00
<b>Card Machine</b> (textile)	2.00	2.50	1.50	Apron, Belt, Disc	1.25	1.50	1.00	Rotary—Coal or Sand	1.50	2.00	1.25
<b>Car Dumpers</b>	2.00	2.50	1.50	Reciprocating	2.00	2.50	1.50	Vibrating	2.00	2.50	2.00
<b>Car Pullers</b>	1.50	2.00	1.25	Screw	1.50	2.00	1.25	<b>Screw Conveyor</b>	1.25	1.50	1.00
<b>Cement Kiln</b>	2.00	2.50	1.50	<b>Filter, Press-Oil</b>	1.50	2.00	1.25	<b>Slab Conveyor</b> (lumber)	1.50	2.00	1.25
<b>Centrifugal, Blower, Fans, Compressors, or Pumps</b>				<b>Generators</b>				<b>Slitters</b> (metal)	1.50	2.00	1.25
1.25	1.50	1.00	Uniform Load	1.25	1.50	1.00	<b>Soapers</b> (textile)	1.25	1.50	1.00	
<b>Chemical Feeders</b>			Varying Load, Hoist	1.50	2.00	1.25	<b>Sorting Table</b> (lumber)	1.50	2.00	1.25	
(sewage)	1.25	1.50	1.00	Welders	2.00	2.50	1.50	<b>Spinner</b> (textile)	1.50	2.00	1.25
<b>Chiller</b> (oil)	1.50	2.00	1.25	<b>Grit Collector</b> (sewage)	1.25	1.50	1.00	<b>Stoker</b>	1.25	1.50	1.00
<b>Chipper</b> (paper)	2.00	2.50	1.50	<b>Hammermills</b>				<b>Suction Roll</b> (paper)	1.50	2.00	1.25
<b>Circular Resaw</b>			Light Duty, Intermittent	1.50	2.00	1.25	<b>Tenter Frames</b> (textile)	1.50	2.00	1.25	
(lumber)	1.50	2.00	1.25	Heavy Duty, Continuous	2.00	2.50	1.50	<b>Tire Building Machines</b>			
<b>Clarifier or Classifier</b>	1.25	1.50	1.00	<b>Hoists</b>				Tire & Tube Press			
<b>Clay Working Mcery</b>	1.50	2.00	1.25	Heavy Duty	2.00	2.50	1.50	<b>Opener</b>	1.25	1.50	1.00
<b>Collectors</b> (sewage)	1.25	1.50	1.00	Medium Duty	1.50	2.00	1.25	<b>Tumbling Barrels</b>	2.00	2.50	1.50
<b>Compressors</b>			Jordan	2.00	2.50	1.50	<b>Washer &amp; Thickener</b>				
Centrifugal, Screw,			Kiln, Rotary	2.00	2.50	1.50	(paper)	1.50	2.00	1.25	
Lobe	1.25	1.50	1.00	<b>Laundry Washer or Tumbler</b>	2.00	2.50	1.50	<b>Winches</b>	1.50	2.00	1.25
Reciprocating			Line Shafts	1.25	1.50	1.00	<b>Winders—Paper, Textile, Wire</b>	1.50	2.00	1.25	
See Note			Log Hall (lumber)	2.00	2.50	1.50	<b>Windlass</b>	1.50	2.00	1.25	
<b>Concrete Mixers</b>	1.50	2.00	1.25	Loom (textile)	1.50	2.00	1.25	<b>Wire</b>			
<b>Converting Machine</b>			<b>Machine Tools, Main Drives</b>	1.50	2.00	1.25	Drawing	2.00	2.50	1.50	
(paper)	1.50	2.00	Mangle (textile)	1.25	1.50	1.00	Winding	1.50	2.00	1.25	
<b>Conveyors</b>			Mash Tubs (distilling)	1.25	1.50	1.00	<b>Woodworking</b>				
Apron, Assembly, Belt,			Meat Grinder	1.50	2.00	1.25	Machinery	1.25	1.50	1.00	
Flight, Oven, Screw	1.25	1.50	<b>Metal Forming</b>								
Bucket	1.50	2.00	Machines	1.50	2.00	1.25					
<b>Cookers—Brewing, Distilling, Food</b>	1.25	1.50	<b>Mills</b>								
Cooling Tower Fans	2.00	2.50	Ball, Pebble, Rod, Tube, Rubber, Tumbling	2.00	2.50	1.50					
Couch (paper)	1.50	2.00	Dryers, Coolers	1.50	2.00	1.25					
<b>Cranes &amp; Hoists<sup>1</sup></b>			<b>Mixers</b>								
Heavy duty mine	2.00	2.50	Concrete, Muller	1.50	2.00	1.25					
Crushers—Cane (sugar), Stone, Ore	2.00	2.50	Banbury	2.00	2.50	1.50					
Cutter-Paper	2.00	2.50	Ore Crusher	2.00	2.50	1.50					
Cylinder (paper)	2.00	2.50	Oven Conveyor	1.25	1.50	1.00					
Dewatering Screen			Planer (metal or wood)	1.50	2.00	1.25					
(sewage)	1.50	2.00									

**Caution:** Applications involving reciprocating engines and reciprocating driven devices are subject to critical rotational speeds which may damage the coupling and/or connected equipment. Contact Lovejoy Engineering with specific requirements.

Note: ■ 1 indicates: If people are transported, Lovejoy does not recommend and will not warranty the use of the coupling.

## Performance Data

### Sleeve Performance Data

**Chart 2**

Characteristics	Temperature Range		Misalignment Capabilities			Torsional Wind-Up
	F°	C°	Angular (in)	Parallel (in)	Axial (in)	in
EDPM – Unless otherwise specified, S-Flex Endurance couplings are supplied with EPDM flexible sleeves. EPDM has good resistance to commonly used chemicals and is generally not affected by dirt or moisture. Color is black.	-30° to 275° F	-34° to 135° C	1°	up to .062	.125	up to 15°
NEOPRENE – Neoprene provides very good performance characteristics for most applications and offers a very good resistance to chemical and oil conditions. Color is black with a green dot.	0° to 200° F	-18° to 93° C	1°	up to .062	.125	up to 15°
HYTREL® – Hytrel is a polyester elastomer designed for high torque and high temperature applications and offers excellent resistance to chemical and oil conditions. Color is orange.	-65° to 250° F	-54° to 121° C	.25°	up to .035	.125	up to 7°

### S-Flex Endurance Nominal Rated Torque Data

**Chart 3**

Size	ID1 - ID2		EPDM			Neoprene			Hytrel <sup>1</sup>		
	Min Bore	Max Bore	Torque		Max	Torque		Max	Torque		Max
			in-lb	Nm	RPM	in-lb	Nm	RPM	in-lb	Nm	RPM
<b>3</b>	0.375	0.875	78	8.81	9,200	60	6.78	9,200	N/A	N/A	N/A
<b>4</b>	0.500	1.000	156	17.63	7,600	120	13.56	7,600	N/A	N/A	N/A
<b>5</b>	0.500	1.188	312	35.26	7,600	240	27.12	7,600	N/A	N/A	N/A
<b>6</b>	0.625	1.438	585	66.09	6,000	450	50.84	6,000	1,800	203.37	6,000
<b>7</b>	0.625	1.625	940	106.20	5,250	725	81.91	5,250	2,875	324.83	5,250
<b>8</b>	0.750	1.938	1,475	166.66	4,500	1,135	128.24	4,500	4,530	511.82	4,500
<b>9</b>	0.875	2.375	2,340	264.38	3,750	1,800	203.37	3,750	7,200	813.49	3,750
<b>10</b>	1.125	2.750	3,735	422.00	3,600	2,875	324.83	3,600	11,350	1 282.38	3,600
<b>11</b>	1.250	3.375	5,889	665.37	3,600	4,530	511.82	3,600	18,000	2 033.73	3,600
<b>12</b>	1.500	3.875	9,360	1057.54	2,800	7,200	813.49	2,800	31,500	3 559.03	2,800
<b>13</b>	2.000	4.500	11,350	1 282.38	2,400	11,350	1 282.38	2,400	47,268	5 340.57	2,400
<b>14</b>	2.000	5.000	18,000	2 033.73	2,200	18,000	2 033.73	2,200	72,480	8 189.15	2,200
<b>16</b>	3.000	5.500	47,250	5 338.54	1,500	N/A	N/A	N/A	N/A	N/A	N/A

Note: ■ 1 indicates: Operating Hytrel within a high service factor application is not recommended.

The S Type coupling consists of two flanges and one sleeve.

#### **S Type Flange - Inch Bore and Keyway UPC Number Selection Table**

Bore	Keyway	5S	6S	7S	8S	9S	10S	11S	12S	13S	14S	16S
<b>1/2</b>	No Keyway	36349	—	—	—	—	—	—	—	—	—	—
<b>1/2</b>	1/8 x 1/16	36067	—	—	—	—	—	—	—	—	—	—
<b>5/8</b>	No Keyway	—	36353	36355	—	—	—	—	—	—	—	—
<b>5/8</b>	3/16 x 3/32	36068	36093	36116	—	—	—	—	—	—	—	—
<b>3/4</b>	No Keyway	—	—	—	36357	—	—	—	—	—	—	—
<b>3/4</b>	3/16 x 3/32	36069	36094	36117	36132	—	—	—	—	—	—	—
<b>13/16</b>	3/16 x 3/32	36070	—	—	—	—	—	—	—	—	—	—
<b>7/8</b>	No Keyway	—	—	—	—	36359	—	—	—	—	—	—
<b>7/8</b>	3/16 x 3/32	36071	36095	36118	36133	36151	—	—	—	—	—	—
<b>15/16</b>	1/4 x 1/8	36072	36096	36119	36134	44363	—	—	—	—	—	—
<b>1</b>	1/4 x 1/8	36073	36097	36120	36135	36152	—	—	—	—	—	—
<b>1-1/16</b>	1/4 x 1/8	36074	36098	36121	44364	45742	46612	—	—	—	—	—
<b>1-1/8</b>	No Keyway	—	—	—	—	—	36361	—	—	—	—	—
<b>1-1/8</b>	1/4 x 1/8	36075	36099	36122	36136	36153	36363	—	—	—	—	—
<b>1-3/16</b>	1/4 x 1/8	36076	36100	36123	36137	—	46613	—	—	—	—	—
<b>1-1/4</b>	No Keyway	—	—	—	—	—	—	36365	—	—	—	—
<b>1-1/4</b>	1/4 x 1/16	36077	—	—	—	—	—	—	—	—	—	—
<b>1-1/4</b>	1/4 x 1/8	—	36101	36124	36138	36154	36171	36189	—	—	—	—
<b>1-5/16</b>	5/16 x 5/32	—	36102	36125	36139	—	—	—	—	—	—	—
<b>1-3/8</b>	5/16 x 5/32	—	36103	36126	36140	36155	36172	36190	—	—	—	—
<b>1-7/16</b>	3/8 x 3/16	—	36104	36127	36141	36156	36173	—	—	—	—	—
<b>1-1/2</b>	No Keyway	—	—	—	—	—	—	—	36367	—	—	—
<b>1-1/2</b>	3/8 x 1/8	—	36105	—	—	—	—	—	—	—	—	—
<b>1-1/2</b>	3/8 x 3/16	—	—	36128	36142	36157	36174	36191	36200	—	—	—
<b>1-9/16</b>	3/8 x 3/16	—	—	—	—	36158	36980	55291	—	—	—	—
<b>1-5/8</b>	3/8 x 3/16	—	36106	—	—	—	—	—	—	—	—	—
<b>1-5/8</b>	3/8 x 3/16	—	—	36129	36143	36159	36175	36192	55059	—	—	—
<b>1-11/16</b>	3/8 x 3/16	—	—	—	36144	36160	36176	49451	—	—	—	—
<b>1-3/4</b>	3/8 x 1/8	—	36107	36130	—	—	—	—	—	—	—	—
<b>1-3/4</b>	3/8 x 3/16	—	—	—	36145	36161	36177	36193	41773	—	—	—
<b>1-7/8</b>	1/2 x 1/8	—	—	36131	—	—	—	—	—	—	—	—
<b>1-7/8</b>	1/2 x 1/4	—	—	—	36146	36162	36178	36194	36201	—	—	—
<b>1-15/16</b>	1/2 x 1/4	—	—	—	36147	36163	36179	49816	56796	—	—	—
<b>2 RSB</b>	No Keyway	—	—	—	—	—	—	—	—	35441	35445	—
<b>2</b>	1/2 x 1/4	—	—	—	—	36164	36180	45158	45672	—	—	—
<b>2</b>	1/2 x 3/16	—	—	—	36148	—	—	—	—	—	—	—
<b>2-1/8</b>	1/2 x 3/16	—	—	—	36149	—	—	—	—	—	—	—
<b>2-1/8</b>	1/2 x 1/4	—	—	—	—	36165	36181	36195	36202	55060	55062	—
<b>2-3/16</b>	1/2 x 1/4	—	—	—	—	36166	36182	—	—	—	—	—
<b>2-1/4</b>	1/2 x 1/4	—	—	—	—	36167	36183	45544	55560	—	—	—
<b>2-3/8</b>	5/8 x 1/8	—	—	—	36150	—	—	—	—	—	—	—
<b>2-3/8</b>	5/8 x 5/16	—	—	—	—	36168	36184	36196	36203	35442	55063	—
<b>2-7/16</b>	5/8 x 5/16	—	—	—	—	—	36185	55229	56808	—	—	—
<b>2-1/2</b>	5/8 x 5/16	—	—	—	—	36169	—	—	—	—	—	—
<b>2-1/2</b>	5/8 x 5/16	—	—	—	—	—	36186	56581	47895	—	—	—
<b>2-3/4</b>	5/8 x 5/16	—	—	—	—	46349	46585	45543	54940	—	—	—
<b>2-7/8</b>	3/4 x 1/8	—	—	—	—	36170	36187	—	—	—	—	—
<b>2-7/8</b>	3/4 x 3/8	—	—	—	—	—	—	36197	36204	35443	35446	—
<b>3 RSB</b>	No Keyway	—	—	—	—	—	—	—	—	—	—	35448
<b>3-3/8</b>	7/8 x 3/16	—	—	—	—	—	36188	—	—	—	—	—
<b>3-3/8</b>	7/8 x 7/16	—	—	—	—	—	—	36198	36205	55061	55064	—
<b>3-7/8</b>	1 x 1/4	—	—	—	—	—	—	36199	—	—	—	—
<b>3-7/8</b>	1 x 1/2	—	—	—	—	—	—	—	36206	—	—	—

Notes: ■ All standard finished bore keyway flanges have 2 set screws @ 90°. Sizes 13,14 and 16 RSB flanges are suitable for reborning and have two set screws @ 90°. Sizes 5-12 RSB flanges have no set screws.

■ When referencing the Lovejoy UPC number in this table, include 685144 as a prefix to the number shown.

## Standard Sleeve, J and S Type Metric Bore / Keyway Item Selection

The J and S Type coupling consists of two flanges and one sleeve.

### S-Flex Endurance Standard Sleeve UPC Number Selection Table

Size	JE	Bulk Pack JE <sup>1</sup>	JES	Bulk Pack JES <sup>1</sup>	JN	JNS	E	Bulk Pack E <sup>1</sup>	N	H	HS
<b>3</b>	36384	52712	36692	52713	35356	36866	—	—	—	—	—
<b>4</b>	35359	52714	36695	52715	35360	36869	—	—	—	—	—
<b>5</b>	35350	52716	36698	52717	35366	36872	35368	52718	35369	—	—
<b>6</b>	35569	52719	36701	52720	35394	36875	35600	52721	36411	40738	40741
<b>7</b>	35570	52722	36704	52723	36398	36878	36414	52724	36416	36848	41704
<b>8</b>	35572	52725	36707	52726	36402	36881	36419	52727	36421	36514	40072
<b>9</b>	36405	—	36864	—	—	—	36424	—	36426	40744	40747
<b>10</b>	35450	—	35451	—	—	—	36429	—	35453	35454	35455
<b>11</b>	—	—	—	—	—	—	36433	—	35457	35458	35459
<b>12</b>	—	—	—	—	—	—	36437	—	35461	35462	35463
<b>13</b>	—	—	—	—	—	—	35464	—	35465	—	35466
<b>14</b>	—	—	—	—	—	—	35467	—	35468	—	35469
<b>16</b>	—	—	—	—	—	—	35470	—	—	—	—

Note: ■ 1 indicates: Bulk pack sizes 3-6 contain ten pieces, sizes 7-8 contain five pieces.

### J and S Type - Metric Bore and Keyway UPC Number Selection Table

Bore	Keyway	3J	4J	5S	6S	7S	8S	9S	10S	11S	12S
<b>9</b>	No Keyway	41485	—	—	—	—	—	—	—	—	—
<b>11</b>	4 x 1.8	41486	—	—	—	—	—	—	—	—	—
<b>12</b>	No Keyway	—	41499	—	—	—	—	—	—	—	—
<b>12</b>	4 x 1.8	41487	—	—	—	—	—	—	—	—	—
<b>14</b>	No Keyway	—	—	41514	—	—	—	—	—	—	—
<b>14</b>	5 x 2.3	41488	41500	41515	—	—	—	—	—	—	—
<b>15</b>	No Keyway	—	—	—	41531	—	—	—	—	—	—
<b>15</b>	5 x 2.3	41489	41501	—	—	—	—	—	—	—	—
<b>16</b>	5 x 2.3	41490	41502	41516	—	—	—	—	—	—	—
<b>19</b>	No Keyway	—	—	—	—	41547	—	—	—	—	—
<b>19</b>	6 x 2.8	41491	41503	41517	41532	56571	—	—	—	—	—
<b>20</b>	6 x 2.8	—	41504	41518	41533	—	—	—	—	—	—
<b>24</b>	No Keyway	—	—	—	—	—	41561	41575	—	—	—
<b>24</b>	8 x 3.3	—	41505	41519	41534	51257	55746	—	—	—	—
<b>25</b>	8 x 3.3	—	—	41520	41535	41548	—	—	—	—	—
<b>28</b>	8 x 3.3	—	—	41521	41536	41549	41562	—	—	—	—
<b>30</b>	8 x 3.3	—	—	—	41537	41550	41563	41576	52258	—	—
<b>32</b>	10 x 3.3	—	—	—	41538	41551	41564	41577	59839	—	—
<b>35</b>	10 x 3.3	—	—	—	41539	49552	—	—	59721	—	—
<b>38</b>	10 x 3.3	—	—	—	55323	41552	41565	41578	45222	59889	—
<b>42</b>	12 x 3.3	—	—	—	—	41553	41566	41579	45883	59888	—
<b>45</b>	14 x 3.8	—	—	—	—	—	41567	46034	48389	—	—
<b>48</b>	14 x 3.8	—	—	—	—	—	41568	41580	59838	59887	—
<b>50</b>	14 x 3.8	—	—	—	—	—	—	—	44380	—	59855
<b>52</b>	16 x 4.3	—	—	—	—	—	—	—	58450	59720	—
<b>55</b>	16 x 4.3	—	—	—	—	—	—	—	45956	64136	—
<b>60</b>	18 x 4.4	—	—	—	—	—	—	—	52009	52711	54955
<b>65</b>	18 x 4.4	—	—	—	—	—	—	—	—	—	54941
<b>70</b>	20 x 4.9	—	—	—	—	—	—	—	—	59886	58725
<b>80</b>	22 x 5.4	—	—	—	—	—	—	—	—	59885	59856
<b>90</b>	25 x 5.4	—	—	—	—	—	—	—	—	—	59857

Notes: ■ Metric Bore / Keyway per DIN specifications. See engineering section in the Lovejoy full line catalog for tolerances (page ED-17 and ED-19).  
■ When referencing the Lovejoy UPC number in this table, include 685144 as a prefix to the number shown.

### Item Selection

The J Type coupling consists of two J flanges and one sleeve.

**J Type Flange - Inch Bore and Keyway UPC Number Selection Table**

Bore	Keyway	3J	4J	5J	6J
<b>3/8</b>	No Keyway	36046	—	—	—
<b>1/2</b>	No Keyway	36114	36115	36347	—
<b>1/2</b>	1/8 x 1/16	36047	36051	36057	—
<b>5/8</b>	No Keyway	—	—	—	36351
<b>5/8</b>	3/16 x 3/32	36048	36052	36058	36078
<b>3/4</b>	3/16 x 3/32	36049	36053	36059	36079
<b>7/8</b>	3/16 x 3/32	36050	36054	36060	36080
<b>15/16</b>	1/4 x 1/8	—	36055	36061	36081
<b>1</b>	1/4 x 1/8	—	36056	36062	36082
<b>1-1/16</b>	1/4 x 1/8	—	—	36063	36083
<b>1-1/8</b>	1/4 x 1/8	—	—	36064	36084
<b>1-3/16</b>	1/4 x 1/8	—	—	—	36085
<b>1-1/4</b>	1/4 x 1/8	—	—	—	36086
<b>1-5/16</b>	5/16 x 5/32	—	—	—	36087
<b>1-3/8</b>	5/16 x 5/32	—	—	—	36088



#### Notes:

- We do not recommend reboring 3J or 4J Flanges.
- See page ED-8 in the Lovejoy full line catalog for standard keyway dimensions.

The SC Type coupling consists of two SCH or SCHS hubs, two SC spacer flanges, and one sleeve.

**SC Type Spacer Flanges**

For Required Shaft Separation <sup>1</sup>	SC Flange Size	Coupling Size														
		5	6	7	8	8-10	9	9-11	10	10-13	11	11-14	12	12-14	13	14
<b>3-1/2</b>	35	36524	36526	36532	36538	36540	36548	—	—	—	—	—	—	—	—	—
<b>4-3/8</b>	44	—	36528	36534	36542	—	36550	—	—	—	—	—	—	—	—	—
<b>4-3/4</b>	48	—	—	—	—	—	—	—	36560	—	36570	—	—	—	—	—
<b>5</b>	50	—	36530	36536	36544	36546	36552	36554	36562	—	36572	—	—	—	—	—
<b>7</b>	70	—	—	—	—	—	—	36556	—	36564	—	36574	36580	38582	—	—
<b>7-3/4</b>	78	—	—	—	—	—	—	36558	—	36566	—	36576	36584	36586	54200	54202
<b>10</b>	100	—	—	—	—	—	—	—	—	36568	—	36578	—	36588	—	—

Note: ■ 1 indicates: See page SF-23 for other lengths possible thru various combinations.

**SCH and SCHS Type - Inch Bore and Keyway UPC Number Selection Table**

Bore	Keyway	5SCH	6SCH	7SCH	8SCH	9SCH	9SCHS	10SCH	10SCHS	11SCH	11SCHS	12SCH	12SCHS	13SCH	13SCHS	14SCH
<b>1/2</b>	No Keyway	36710	—	—	—	—	—	—	—	—	—	—	—	—	—	—
<b>1/2</b>	1/8 x 1/16	36711	—	—	—	—	—	—	—	—	—	—	—	—	—	—
<b>5/8</b>	No Keyway	—	36712	—	36714	—	—	—	—	—	—	—	—	—	—	—
<b>5/8</b>	3/16 x 3/32	36590	36713	36715	—	—	—	—	—	—	—	—	—	—	—	—
<b>3/4</b>	No Keyway	—	—	—	36718	—	—	—	—	—	—	—	—	—	—	—
<b>3/4</b>	3/16 x 3/32	36591	36600	36716	36719	—	—	—	—	—	—	—	—	—	—	—
<b>7/8</b>	No Keyway	—	—	—	—	36721	36910	—	—	—	—	—	—	—	—	—
<b>7/8</b>	3/16 x 3/32	36592	36601	36612	36624	36722	—	—	—	—	—	—	—	—	—	—
<b>1</b>	1/4 x 1/8	36593	36602	36613	36625	36640	—	—	—	—	—	—	—	—	—	—
<b>1-1/8</b>	No Keyway	—	—	—	—	—	—	36729	36912	36737	36914	—	—	—	—	—
<b>1-1/8</b>	1/4 x 1/8	36594	36603	36614	36626	36641	36682	36728	36684	36738	36686	—	—	—	—	—
<b>1-1/4</b>	1/4 x 1/8	—	36604	36717	36720	36723	36725	59905	36733	—	36741	—	—	—	—	—
<b>1-3/8</b>	5/16 x 5/32	—	36605	36615	36627	36642	36726	56486	36734	—	36742	—	—	—	—	—
<b>1-1/2</b>	3/8 x 3/16	—	—	36616	36628	36643	36727	59906	36735	59908	36743	—	—	—	—	—
<b>1-5/8</b>	3/8 x 3/16	—	—	36617	36629	36644	—	36656	36736	54909	36687	—	—	—	—	—
<b>1-3/4</b>	3/8 x 3/16	—	—	—	36630	36645	—	36730	—	59909	—	—	—	—	—	—
<b>1-7/8</b>	1/2 x 1/4	—	—	—	36631	36646	—	36657	—	36664	—	36745	36747	—	—	—
<b>2</b>	1/2 x 1/4	—	—	—	—	36724	—	36731	—	36739	—	—	36748	—	—	—
<b>2-1/8</b>	1/2 x 1/4	—	—	—	—	36647	—	36658	—	36665	—	36672	36749	—	36756	—
<b>2-1/4</b>	1/2 x 1/4	—	—	—	—	—	—	36732	—	36740	—	36746	36750	—	—	—
<b>2-3/8</b>	5/8 x 5/16	—	—	—	—	—	—	36659	—	36666	—	36673	—	36752	36757	36759
<b>2-7/8</b>	3/4 x 3/8	—	—	—	—	—	—	—	—	36667	—	36674	—	36753	—	36760
<b>3-3/8</b>	7/8 x 7/16	—	—	—	—	—	—	—	—	—	—	—	—	36754	—	36761
<b>3-7/8</b>	1 x 1/2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	36762

Note: ■ When referencing the Lovejoy UPC number in this table, include 685144 as a prefix to the number shown.

**Ratings****Performance Data****S-Flex Endurance Performance Ratings**

Size	Sleeve Material	Basic HP Ratings @ Varying RPM				Torque Rating		Torsional <sup>1</sup> Stiffness in-lb/rad	Max Bore		Max RPM
		100	1200	1800	3600	in-lbs	Nm		in	mm	
<b>3</b>	EPDM	0.1	1.4	2.2	4.4	78	8.81	298	0.875	22	9,200
	Neoprene	0.1	1.1	1.7	3.4	60	6.78	229	0.875	22	9,200
<b>4</b>	EPDM	0.2	3.0	4.4	9.0	156	17.63	595	1.000	25	7,600
	Neoprene	0.2	2.3	3.4	6.9	120	13.56	458	1.000	25	7,600
<b>5</b>	EPDM	0.5	6.0	9.0	17.8	312	35.26	1,191	1.188	30	7,600
	Neoprene	0.4	4.6	6.9	13.7	240	27.12	916	1.188	30	7,600
<b>6</b>	EPDM	0.9	11.2	16.8	33.4	585	66.09	2,233	1.438	38	6,000
	Neoprene	0.7	8.6	12.9	25.7	450	50.84	1,718	1.438	38	6,000
<b>6H</b>	Hytrel	2.9	34.0	51.0	103.0	1,800	203.37	10,000	1.438	38	6,000
<b>7</b>	EPDM	1.6	18.2	27.3	53.3	940	106.20	3,600	1.625	42	5,250
	Neoprene	1.2	14.0	21.0	41.0	725	81.91	2,769	1.625	42	5,250
<b>7H</b>	Hytrel	4.6	55.0	82.0	164.0	2,875	324.83	20,000	1.625	42	5,250
<b>8</b>	EPDM	2.3	28.6	41.6	84.5	1,475	166.66	5,636	1.938	49	4,500
	Neoprene	1.8	22.0	32.0	65.0	1,135	128.24	4,335	1.938	49	4,500
<b>8H</b>	Hytrel	7.2	86.0	129.0	259.0	4,530	511.82	30,000	1.938	49	4,500
<b>9</b>	EPDM	3.8	44.2	66.3	133.9	2,340	264.38	8,938	2.375	60	3,750
	Neoprene	2.9	34.0	51.0	103.0	1,800	203.37	6,875	2.375	60	3,750
<b>9H</b>	Hytrel	11.4	137.0	206.0	411.0	7,200	813.49	47,500	2.375	60	3,750
<b>10</b>	EPDM	6.0	71.5	106.6	213.2	3,735	422.00	14,274	2.750	70	3,600
	Neoprene	4.6	55.0	82.0	164.0	2,875	324.83	10,980	2.750	70	3,600
<b>10H</b>	Hytrel	18.0	216.0	324.0	648.0	11,350	1 282.38	100,000	2.750	70	3,600
<b>11</b>	Neoprene	7.2	86.0	129.0	259.0	4,530	511.82	17,300	3.375	86	3,600
	EPDM	9.4	111.8	167.7	336.7	5,889	665.37	22,490	3.375	86	3,600
<b>11H</b>	Hytrel	28.6	343.0	514.0	1,028.0	18,000	2 033.73	12,500	3.375	86	3,600
<b>12</b>	Neoprene	11.4	137.0	206.0	—	7,200	813.49	27,500	3.875	99	2,800
	EPDM	14.8	178.1	267.8	—	9,360	1057.54	35,750	3.875	99	2,800
<b>12H</b>	Hytrel	50.0	600.0	900.0	—	31,500	3 559.03	225,000	3.875	99	2,800
<b>13</b>	EPDM & Neoprene	18.0	216.0	324.0	—	11,350	1 282.38	43,350	4.500	114	2,400
<b>13H</b>	Hytrel	75.0	900.0	1,350.0	—	47,268	5 340.57	368,900	4.500	114	2,400
<b>14</b>	EPDM & Neoprene	28.6	343.0	514.0	—	18,000	2 033.73	68,755	5.000	127	2,200
<b>14H</b>	Hytrel	115.0	1,380.0	2,070.0	—	72,480	8 189.15	593,250	5.000	127	2,200
<b>16</b>	EPDM	75.0	900.0	—	—	47,250	5 338.54	180,480	5.500	140	1,500

Notes: ■ 1 indicates: Values shown are for an ambient temperature of 75° F (24° C).

■ Coupling ratings are based on sleeve material regardless of flange design.

## Sleeves


### Dimensional Data

#### S-Flex Endurance Sleeve Types


##### S-Flex Endurance Sleeves

- Flexible sleeves for Lovejoy S-Flex Endurance couplings are available in three materials (EPDM, Neoprene, and Hytrel®) and in three basic designs: one piece solid, one-piece split, or two piece

**NOW  
IMPROVED!**



JE, JN, JES and JNS Types



E and N Types

##### JE, JN, JES and JNS Types

- JE and JN Type sleeves feature a one-piece solid design
- JES and JNS Type sleeves feature a one-piece split design
- JE and JES Type sleeves are molded in EPDM material
- JN and JNS Type sleeves are molded in Neoprene material


SFE

##### E and N Types

- E and N Type sleeves feature a two-piece design with retaining ring
- E Type sleeves are made from EPDM material and are available in sizes 5-16
- N Type sleeves are made from Neoprene material and are available in sizes 5-14
- Two piece sleeves are ideal for applications where small shaft separations inhibit the installation of a one piece sleeve

##### H and HS Types

- H and HS Type sleeves are designed for high torque applications, transmitting about 3 to 4 times as much power as an equivalent EPDM or Neoprene sleeve
- Hytrel sleeves are available in a one-piece solid (H) or two-piece split (HS) construction
- Hytrel sleeves can be used only with S or SC flanges and can not be used with J or B flanges
- Hytrel sleeves should not be used as direct replacements for EPDM or Neoprene applications
- H and HS Type sleeves are available for sizes 6-14 (sizes 13 and 14 are available in HS only)



H and HS Types

#### Sleeve Dimensional Data

Size	Types JE, JES, JN & JNS			Types E & N			Types H & HS		
	EPDM & Neoprene			EPDM & Neoprene			Hytrel		
	L in	OD in	Weight lbs	L in	OD in	Weight lbs	L in	OD in	Weight lbs
3	1.00	1.88	0.06	—	—	—	—	—	—
4	1.25	2.31	0.10	—	—	—	—	—	—
5	1.56	2.94	0.20	1.56	2.94	0.25	—	—	—
6	1.88	3.75	0.40	1.88	3.75	0.49	1.88	3.75	0.44
7	2.19	4.34	0.62	2.19	4.34	0.77	2.19	4.34	0.69
8	2.50	5.06	1.13	2.50	5.06	1.40	2.50	5.06	1.40
9	3.00	6.00	1.46	3.00	6.00	2.00	3.00	6.00	1.80
10	3.44	7.06	2.32	3.44	7.06	3.20	3.44	7.06	2.90
11	—	—	—	4.00	8.19	5.10	4.00	8.19	4.50
12	—	—	—	4.69	9.56	8.10	4.69	8.56	7.30
13	—	—	—	5.50	11.19	13.00	5.50	11.19	11.80
14	—	—	—	6.50	13.09	21.10	6.50	13.09	19.30
16	—	—	—	8.75	17.91	45.30	—	—	—

Note: ■ See page SF-13 for Performance Data.


## J Type

### Dimensional Data

#### J Type Flanges and J Type Couplings

##### J Type Flanges

- The J Type flanges in sizes 3J and 4J are made from die cast of high strength zinc alloy (tensile strength of 41,000 psi) and are furnished bore-to-size
- Size 5J is provided in either zinc alloy or cast iron depending on the bore size
- Size 6J is made from cast iron
- J flanges are compatible with EPDM or Neoprene sleeves
- Each flange has a keyway and two set screws (one set screw over the key and one at 90° to the keyway)




**J Type Flange**

SFE

##### J Type Coupling

- Complete S-Flex Endurance couplings, with J Type flanges described above, are normally supplied with the one-piece JE sleeve or the one-piece split JES sleeve. An optional JN (Neoprene, one-piece) sleeve or the one-piece split JNS sleeve
- Sizes 5J and 6J couplings are also available with E and N two piece sleeves



**J Type Coupling**

#### J Type Dimensional Data

Size	Max Bore with Standard Keyway	L	FL	P	SL	OD	T	HD	OAL	G <sup>1</sup>	R	Weight	
		in	in	in	in	in	in	in	in	in	in	Flange	Coupling
<b>3J</b>	0.875	0.81	0.38	0.44	0.25	2.062	1/4-20	1.50	2.00	0.44	0.56	0.30	0.68
<b>4J</b>	1.000	0.88	0.44	0.44	0.25	2.460	1/4-20	1.63	2.38	0.63	0.75	0.40	0.89
<b>5J</b>	1.125	1.06	0.59	0.47	0.29	3.250	1/4-20	1.88	2.88	0.75	0.97	1.10	2.40
<b>6J</b>	1.375	1.31	0.78	0.53	0.29	4.000	5/16-18	2.50	3.50	0.88	1.09	1.90	4.36

Notes: ■ 1 indicates: Spacing between shafts should be greater than 1/8 inch and less than OAL minus the sum of the two bore dimensions.

■ See page SF-13 for Performance Data.

## S Type

### Dimensional Data

#### S Type Flanges and S Type Couplings


##### S Type Flanges

- S flanges are made of high strength cast iron and are bored-to-size for a slip fit on standard shafts
- S flanges are easy to install, are readily available from stock in a wide range of popular bore sizes, and are supplied with two set screws at 90°

##### S Type Couplings

- S Type couplings, normally supplied with the two-piece E sleeve, can be used with any JE, JN, N, H, or HS sleeves

SFE



**S Type Flange**

**S Type Coupling**

#### S Type Dimensional Data

Size	ID1		L	FL	P	SL	OD	T	HD	OAL	G	R	Weight Flange
	Max Bore Standard Keyway	Max Bore Shallow Keyway											
<b>5S</b>	1.188	1.250	1.34	0.59	0.45	0.29	3.250	1/4-20	1.88	2.81	0.75	0.97	1.1
<b>6S</b>	1.438	1.500	1.64	0.78	0.53	0.29	4.000	5/16-18	2.50	3.50	0.88	1.09	1.9
	—	1.750	1.64	0.78	0.53	—	4.000	—	2.50	3.50	0.88	1.09	1.8
<b>7S</b>	1.625	1.875	1.84	0.80	0.67	0.35	4.625	3/8-16	2.81	3.94	1.00	1.31	2.6
<b>8S</b>	1.938	2.250	2.10	0.88	0.75	0.38	5.450	3/8-16	3.25	4.39	1.13	1.50	4.4
	—	2.375	1.94	0.88	1.03	—	5.450	—	3.25	4.95	1.13	1.50	3.7
<b>9S</b>	2.375	2.500	2.41	1.03	0.78	0.41	6.350	1/2-13	3.63	5.06	1.44	1.75	6.5
	—	2.875	2.28	1.03	1.25	—	6.350	—	4.13	6.00	1.44	1.75	6.2
<b>10S</b>	2.750	3.125	2.70	1.22	0.81	0.41	7.500	1/2-13	4.38	5.69	1.63	2.00	10.5
	—	3.375	2.70	1.22	0.81	—	7.500	—	4.75	5.69	1.63	2.00	9.8
<b>11S</b>	3.375	3.625	3.44	1.50	1.13	0.56	8.625	1/2-13	5.25	7.13	1.88	2.38	16.6
	—	3.875	3.06	1.50	1.56	—	8.625	—	5.63	8.00	1.88	2.38	16.4
<b>12S</b>	2.875	—	4.00	1.69	1.28	0.63	10.000	1/2-13	4.88	8.25	2.31	2.69	27.5
	3.875	3.938	4.00	1.69	1.28	—	10.000	—	5.75	8.25	2.31	2.69	26.6
<b>13S</b>	4.500	—	4.38	1.97	1.31	0.81	11.750	5/8-11	6.75	9.25	2.69	3.06	45.0
<b>14S</b>	5.000	—	4.50	2.25	1.06	0.62	13.875	5/8-11	7.50	9.88	3.25	3.50	69.0
<b>16S</b>	5.500	6.000	6.00	2.75	2.00	1.00	18.875	5/8-11	8.00	14.50	4.75	4.25	125.0


Notes:

- Spacing between shafts should be greater than 1/8 inch and less than OAL minus the sum of the two bore dimensions.

- See page SF-13 for Performance Data.

- The sizes with two dimensions listed indicate measurements for standard flanges (1st Line) and modified spacer flanges (2nd Line). See page SF-21.

- To determine shaft separation (BSE), use the formula  $BSE = OAL - (2 \times L)$ .



**S Type**



**S Type with E Sleeve**

SFE

#### S Type Shallow Keyway Dimensional Data

Size	L in	ID1		HD in	Shallow Keyway Dimensions								
		Max Bore Standard Keyway	Max Bore Shallow Keyway		Bore in	Keyway in	Key in	Bore in	Keyway in	Key in	Bore in	Keyway in	Key in
		in	in		in	in	in	in	in	in	in	in	in
<b>5S</b>	1.34	1.188	1.250	1.88	1.25	.25 x .06	.25 x .19 x 1.38	—	—	—	—	—	—
<b>6S</b>	1.63	1.438	1.500	2.50	1.50	.38 x .13	.38 x .31 x 1.5	—	—	—	—	—	—
	1.31	—	1.750	2.50	1.56-1.63	.38 x .13	.38 x .31 x 1.31	1.69-1.75	.38 x .06	.38 x .25 x 1.25	—	—	—
<b>7S</b>	1.84	1.625	1.875	2.81	1.69-1.75	.38 x .13	.38 x .31 x 1.81	1.81-1.88	.5 x .13	.5 x .38 x 1.81	—	—	—
<b>8S</b>	2.09	1.938	2.250	3.25	2-2.25	.5 x .19	.5 x .44 x 2.06	—	—	—	—	—	—
	1.94	—	2.375	3.25	—	—	—	2.31-2.38	.63 x .13	.63 x .44 x 1.88	—	—	—
<b>9S</b>	2.41	2.375	2.500	3.63	2.44-2.5	.63 x .19	.63 x .5 x 2.38	—	—	—	—	—	—
	2.28	—	2.875	4.13	—	—	—	2.56-2.75	.63 x .19	.63 x .5 x 2.25	2.81-2.88	.75 x .13	.75 x .5 x 2.25
<b>10S</b>	2.72	2.750	3.125	4.38	2.81-3.13	.75 x .13	.75 x .5 x 2.75	—	—	—	—	—	—
	2.69	—	3.375	4.75	—	—	—	3.18-3.25	.75 x .13	.75 x .5 x 2.63	3.31-3.38	.88 x .19	.88 x .63 x 2.63
<b>11S</b>	3.44	3.375	3.625	5.25	3.44-3.63	.88 x .19	.88 x .63 x 3.44	—	—	—	—	—	—
	3.06	—	3.875	5.63	—	—	—	3.69-3.75	.88 x .19	.88 x .63 x .3	3.88	1 x .25	1 x .75 x 3
<b>12S</b>	4.00	2.875	—	4.88	—	—	—	—	—	—	—	—	—
	4.00	3.875	3.938	5.75	3.94	1 x .13	1 x .63 x 4	—	—	—	—	—	—
<b>13S</b>	4.38	4.500	—	6.75	—	—	—	—	—	—	—	—	—
<b>14S</b>	4.50	5.000	—	7.50	—	—	—	—	—	—	—	—	—
<b>16S</b>	6.00	5.500	6.000	8.00	5.56-6	1.5 x .25	1.5 x 1 x 6	—	—	—	—	—	—

Notes: ■ Some large bore S Type flanges are supplied with shallow keyways as standard. Rectangular keystock is provided for stock bores only.  
■ See page SF-13 for Performance Data.

## B Type with Bushings

### Dimensional Data

#### B Type Flanges For Use With Bushings

##### B Type Flange


- Model B (bushed) flanges are made of the same high-strength cast iron as the S flanges
- B flanges are designed to accommodate the industry standard bushing for easy installation and removal
- B flanges are available in sizes 6 through 16

##### Couplings

- S-Flex Endurance couplings with B flanges (for use with bushings) are normally supplied with the two-piece E sleeve
- The B style flanges can be used with any of the sleeves pictured on SF-5, with the exception of the Hytrex® sleeve
- B flanges can be used in combination with S Type flanges


##### Bushings

- Bushings have a split design that allow for a compression fit for secure mounting of the flange to the shaft without set screws
- The bushing's clamp-like fit creates a one-piece assembly to eliminate wobble, vibration, and fretting corrosion
- Slightly oversized or undersized shafts can be accommodated with the same secure grip
- The design prevents potentially hazardous key drift on applications subject to pulsation or vibration
- B flanges are bored to accept a bushing accommodating many bore sizes, thus reducing inventory and increasing coupling versatility
- For bushing bore information contact your Customer Service Representative



**B Type Flange**

**B Type Coupling**



#### B Type Flange and Coupling Dimensional Data

Size	Flange UPC Number	Bushing Required	L1	L2	FL	P	OD	HD	OAL	G	R Max	Approx Bore in	Flange Weight lbs
			in	in	in	in	in	in	in	in	in	in	
<b>6B</b>	36369	JA	1.53	1.00	0.78	0.44	4.000	2.00	3.31	0.88	1.09	1.19	1.3
<b>7B</b>	36371	JA	1.59	1.00	0.78	0.44	4.625	2.00	3.44	1.00	1.31	1.19	1.9
<b>8B</b>	36373	SH	1.84	1.25	0.91	0.50	5.450	2.69	3.94	1.13	1.50	1.63	2.9
<b>9B</b>	36375	SD	2.19	1.81	1.03	0.56	6.350	3.19	4.63	1.44	1.75	1.94	4.8
<b>10B</b>	35421	SK	1.84	1.88	1.22	0.63	7.500	3.88	5.31	1.63	2.00	2.50	7.8
<b>11B</b>	35432	SF	2.13	2.00	1.50	0.63	8.625	4.63	6.13	1.88	2.31	2.38	12.0
<b>12B</b>	36408	E	2.69	2.63	1.69	0.88	10.000	6.00	7.44	2.31	2.69	3.44	18.0
<b>13B</b>	35444	F	3.69	3.63	1.97	1.00	11.750	6.63	8.63	2.69	3.00	3.94	31.2
<b>14B</b>	35447	F	3.69	3.63	2.25	1.00	13.875	6.63	9.75	3.25	3.50	3.94	51.4
<b>16B</b>	35449	J	4.75	4.50	2.75	1.19	18.875	7.25	12.63	4.75	4.25	4.50	120.0

Note: ■ 1 indicates: Spacing between shafts should be greater than 1/8 inch and less than G.  
Spacing between internal face of flange should be OAL – (2 x L1).

■ Bushings are not available from Lovejoy.

#### Bushing Dimensional Data

Size	L	P	FL	T	HD	D	ID1 - ID2			Number & Size of Cap		Cap Screw Torque	Weight
							Min Bore Std Keyway in	Max Bore Std Keyway in	Max Bore Shallow Keyway2 in	Qty	Size		
<b>JA</b>	1.00	0.69	0.31	0.56	2.00	1.375	0.50	1.00	1.19	3	#10 - 1	5	0.8
<b>SH</b>	1.25	0.88	0.38	0.81	2.68	1.871	0.50	1.38	1.63	3	1/4 - 1-3/8	9	0.9
<b>SD</b>	1.81	1.38	0.44	1.25	3.18	2.187	0.50	1.63	1.94	3	1/4 - 1-13/16	9	1.6
<b>SK</b>	1.87	1.38	0.50	1.25	3.88	2.812	0.50	2.13	2.50	3	5/16 - 2	15	2.8
<b>SF</b>	2.00	1.50	0.50	1.25	4.63	3.125	0.50	2.31	2.81	3	3/8 - 2	30	3.9
<b>E</b>	2.63	1.88	0.75	1.63	6.00	3.834	0.88	2.88	3.50	3	1/2 - 2-3/4	60	8.5
<b>F</b>	3.63	2.81	0.81	2.50	6.63	4.438	1.00	3.25	3.94	3	9/16 - 3-5/8	75	13.9
<b>J</b>	4.50	3.50	1.00	3.19	7.25	5.148	1.44	3.75	4.50	3	5/8 - 4-1/2	135	21.6

Notes: ■ Bushings are not available from Lovejoy. F bushings are available commercially in a bore range of 1 inch to 4 inches; J bushings in a range of 1-7/8 inches to 4-1/2 inches.

■ Rectangular keys are furnished at no charge when shallow keyway is necessary.  
■ See page SF-13 for Performance Data.


## T Type

### Dimensional Data

#### T Type Flanges For Use With Taper-Lock® Bushings

##### TF Type Flanges

- Model TF flanges are made from the same high-strength cast iron as the S flanges, but are designed to accommodate the international standard Taper Lock bushing for easy installation and removal
- TF Type flanges allow for mounting the bushing on the front (hub) side of the flange
- TF flanges are available in sizes 6 through 16 and can be used with any style of sleeve as pictured on page SF-5



##### TR Type Flanges

- TR flanges are similar to the TF style, but allow for the Taper Lock Bushing to be mounted and removed from the reverse or serration side of the flange
- The limited torque ratings of the Taper Lock Bushings allow TR flanges to only be used with EPDM or Neoprene sleeves
- Different bushing sizes are used, so they have different maximum bores than the TF flanges
- Sizes 6 through 16 are available

Note: ■ Be sure to determine if the bushing being used has either UNC threads (60°) or British Standard Whitworth B.S.W. threads (55°). In the U.S.A. the UNC type is predominant for both inch and metric bores. Outside of the U.S.A. it is most common to see B.S.W., especially on metric bores.

SFE

##### Taper-Lock Bushings

- The industry standard taper lock bushing is a split design allowing a compression fit of the flange to the shaft without set screws
- The simple design makes the installation and removal easy while the 8° taper grips tight and provides excellent concentricity
- A reduced level of inventory can be achieved due to the many other power transmission components that use Taper Lock Bushings such as: sheaves, sprockets, and pulleys
- Lovejoy does not offer the Taper-Lock Bushings themselves as these are widely available from other manufacturers

#### Taper Dimensional Data (Front Mount)

Size	UNC Flange UPC Number	BSW Flange UPC Number	OAL	G	ID1 - ID2		R	OD	L	FL	P	HD	Bushing Screw Size in	Flange Weight lbs	Bushing Required*
					in	mm									
<b>6TF</b>	62265	62263	4.00	0.88	1.25	31	1.09	4.00	1.56	0.78	0.78	2.81	3/8 - 16	1.8	1215/1210
<b>7TF</b>	62269	62267	3.94	1.00	1.25	31	1.31	4.62	1.84	0.78	0.69	2.81	3/8 - 16	2.6	1215/1210
<b>8TF</b>	62273	62271	5.00	1.13	1.62	42	1.50	5.45	1.94	0.91	1.03	3.25	3/8 - 16	3.7	1615/1610
<b>9TF</b>	62277	62275	6.00	1.44	2.00	50	1.75	6.35	2.28	1.03	1.25	4.13	7/16 - 14	6.2	2012
<b>10TF</b>	62281	62279	7.00	1.63	2.50	64	2.00	7.50	2.69	1.22	1.47	4.75	1/2 - 13	9.8	2517
<b>11TF</b>	62285	62283	8.00	1.88	2.50	64	2.38	8.63	3.06	1.50	1.56	5.63	1/2 - 13	16.4	2517
<b>12TF</b>	62289	62287	8.25	2.31	3.00	76	2.69	10.00	4.00	1.69	1.28	5.75	5/8 - 11	26.6	3030
<b>13TF</b>	62293	62294	9.25	2.69	3.00	76	3.06	11.75	4.38	1.97	1.31	6.75	5/8 - 11	45.0	3030
<b>14TF</b>	62297	62295	9.88	3.25	3.94	100	3.50	13.88	4.50	2.25	1.06	7.50	1/2 - 13	69.0	3535
<b>16TF</b>	62301	62299	14.50	4.75	4.44	112	4.25	18.88	6.00	2.75	2.00	8.00	5/8 - 11	125.0	4040

#### Taper Dimensional Data (Rear Mount)

Size	UNC Flange UPC Number	BSW Flange UPC Number	OAL	G	ID1 - ID2		R	OD	L	FL	P	HD	Bushing Screw Size in	Flange Weight lbs	Bushing Required*
					in	mm									
<b>6TR</b>	62266	62264	4.00	0.88	1.00	25	1.09	4.00	1.56	0.78	0.78	2.81	1/4 - 20	1.8	1008
<b>7TR</b>	62270	62268	3.94	1.00	1.12	28	1.31	4.62	1.84	0.78	0.69	2.81	1/4 - 20	2.6	1108
<b>8TR</b>	62274	62272	5.00	1.13	1.25	31	1.50	5.45	1.94	0.91	1.03	3.25	3/8 - 16	3.7	1215/1210
<b>9TR</b>	62278	62276	6.00	1.44	1.62	42	1.75	6.35	2.28	1.03	1.25	4.13	3/8 - 16	6.2	1615/1610
<b>10TR</b>	62282	62280	7.00	1.63	1.62	42	2.00	7.50	2.69	1.22	1.47	4.75	3/8 - 16	9.8	1615/1610
<b>11TR</b>	62286	62284	8.00	1.88	2.50	64	2.38	8.63	3.06	1.50	1.56	5.63	1/2 - 13	16.4	2525
<b>12TR</b>	62290	62288	8.25	2.31	2.50	64	2.69	10.00	4.00	1.69	1.28	5.75	1/2 - 13	26.6	2517
<b>13TR</b>	62294	62292	9.25	2.69	3.00	76	3.06	11.75	4.38	1.97	1.31	6.75	5/8 - 11	45.0	3030
<b>14TR</b>	62298	62296	9.88	3.25	3.00	76	3.50	13.88	4.50	2.25	1.06	7.50	5/8 - 11	69.0	3030
<b>16TR</b>	62302	62300	14.50	4.75	4.44	112	4.25	18.88	6.00	2.75	2.00	8.00	5/8 - 11	125.0	4040

Notes: ■ All above data refers to both standard UNC and British Standard Whitworth B.S.W. threads. Flanges are not supplied with screws.

■ \* indicates that use of a 1210 or 1610 bushing reduces the reserve factor between bushing torque rating and that of the coupling.

■ Taper-Lock® is a registered trademark of Reliance Electric Industrial Company in the United States and Canada. It is a registered trademark of JH Fenner and Co. in the United Kingdom.

■ See page SF-13 for Performance Data.

## SC Type

## Dimensional Data


## SC Type Spacer Couplings

## SC Type Spacer Couplings

- Specifically designed for the pump industry, this coupling accommodates industry standard as well as special pump/motor separation
- This shaft separation facilitates easy pump repair of pump packing, bearings, and seals without disturbing pump or motor mounting and alignment
- The SC Type coupling consists of two flanges, a sleeve and two shaft hubs

## Quick Coupling Removal

- The center drop out section consists of two flanges and the flexible sleeve
- The flange is bolted to the shaft hub with four hex head cap screws
- The center drop out section can be removed by removing the hex head cap screws
- Flats on each hub provides a convenient grip for a wrench in order to facilitate loosening of the screws and, if desired, turning of the pump/motor shafts
- Once the hub is removed from the pump shaft, maintenance on the pump can be done without disturbing equipment alignment




## SC Type (Spacer) Dimensional Data

Size	For Required Shaft Separation in	Use Flange Number	Use Hub Number	OAL <sup>2</sup>	G in	R in	OD in	Weight Complete Coupling <sup>2</sup>	
								in	Ibs
<b>5SC</b>	3.50	5SC35	5SCH	5.63	0.75	0.56	3.250		4.5
<b>6SC</b>	3.50	6SC35	6SCH	5.88	0.88	0.75	4.000		7.3
	4.38	6SC44	6SCH	6.75	0.88	0.75	4.000		8.1
<b>7SC</b>	5.00	6SC50	6SCH	7.38	0.88	0.75	4.000		8.7
	3.50	7SC35	7SCH	6.38	1.00	0.63	4.625		9.9
<b>8SC</b>	4.38	7SC44	7SCH	7.25	1.00	0.63	4.625		10.8
	5.00	7SC50	7SCH	7.88	1.00	0.63	4.625		11.4
<b>9SC</b>	3.50	8SC35	8SCH	6.88	1.13	0.81	5.450		15.2
	3.50	8SC35-10	10SCH <sup>1</sup>	8.13	1.13	0.81	5.450		23.2
<b>10SC</b>	4.38	8SC44	8SCH	7.75	1.13	0.81	5.450		16.4
	5.00	8SC50	8SCH	8.38	1.13	0.81	5.450		17.4
<b>11SC</b>	5.00	8SC50-10	10SCH <sup>1</sup>	9.63	1.13	1.19	5.450		27.2
	3.50	9SC35	9SCH <sup>1</sup>	7.50	1.44	1.06	6.350		18.6
<b>12SC</b>	5.00	9SC50	9SCH <sup>1</sup>	8.88	1.44	1.06	6.350		23.2
	5.00	9SC50-11	11SCH <sup>1</sup>	10.38	1.44	1.19	6.350		40.4
<b>13SC</b>	7.00	9SC70-11	11SCH <sup>1</sup>	12.38	1.44	1.19	6.350		48.2
	7.75	9SC78-11	11SCH <sup>1</sup>	13.13	1.44	1.19	6.350		51.0
<b>14SC</b>	4.75	10SC48	10SCH <sup>1</sup>	9.38	1.63	1.19	7.500		37.6
	5.00	10SC50	10SCH <sup>1</sup>	9.63	1.63	1.19	7.500		38.4
<b>15SC</b>	7.00	10SC70-13	13SCH <sup>1</sup>	13.63	1.63	1.88	7.500		72.0
	7.75	10SC78-13	13SCH <sup>1</sup>	14.38	1.63	1.88	7.500		76.0
<b>16SC</b>	10.00	10SC100-13	13SCH <sup>1</sup>	16.63	1.63	1.88	7.500		88.0
	4.75	11SC48	11SCH <sup>1</sup>	10.31	1.88	1.19	8.625		54.5
<b>17SC</b>	5.00	11SC50	11SCH <sup>1</sup>	10.38	1.88	1.19	8.625		54.7
	7.00	11SC70-14	14SCH	14.63	1.88	2.00	8.625		86.1
<b>18SC</b>	7.75	11SC78-14	14SCH	15.38	1.88	2.00	8.625		90.3
	10.00	11SC100-14	14SCH	17.63	1.88	2.00	8.625		102.7
<b>19SC</b>	7.00	12SC70	12SCH <sup>1</sup>	12.88	2.31	1.50	10.000		88.1
	7.00	12SC70-14	14SCH	14.63	2.31	2.00	10.000		99.1
<b>20SC</b>	7.75	12SC78	12SCH <sup>1</sup>	13.63	2.31	1.50	10.000		91.9
	7.75	12SC78-14	14SCH	15.38	2.31	2.00	10.000		103.3
<b>21SC</b>	7.75	13SC78	13SCH <sup>1</sup>	14.38	2.69	1.88	11.750		129.6
<b>22SC</b>	7.75	14SC78	14SCH	15.38	3.25	2.00	13.875		179.9

Notes : ■ 1 indicates: SC Hubs are available in: SC= Standard Length      SCHS= Short Length.

■ 2 indicates: OAL dimension and weight will vary if one or two short (HS) hubs are used.

■ See page SF-13 for Performance Data.




**SC Type (Spacer) Flange Dimensional Data**

Size	Flange Number	For Required Shaft Separation <sup>1</sup>	SC Hub Number	L	FL	P	OD	HD	Weight Each Flange
				in	in	in	in	in	lbs
<b>5SC</b>	5SC35	3.50	5SCH	1.69	0.59	0.80	3.250	2.00	1.3
	6SC35	3.50	6SCH	1.63	0.72	0.59	4.000	2.50	2.0
<b>6SC</b>	6SC44	4.38	6SCH	2.06	0.72	1.03	4.000	2.50	2.4
	6SC50	5.00	6SCH	2.38	0.72	1.34	4.000	2.50	2.7
<b>7SC</b>	7SC35	3.50	7SCH	1.63	0.78	0.47	4.625	2.81	2.5
	7SC44	4.38	7SCH	2.06	0.78	0.91	4.625	2.81	3.0
	7SC50	5.00	7SCH	2.38	0.78	1.22	4.625	2.81	3.3
<b>8SC</b>	8SC35	3.50	8SCH	1.63	0.91	0.28	5.450	3.25	3.7
	8SC35-10	3.50	10SCH(HS)	1.63	0.91	0.28	5.450	4.38	3.5
	8SC44	4.38	8SCH	2.06	0.91	0.72	5.450	3.25	4.3
	8SC50	5.00	8SCH	2.38	0.91	1.03	5.450	3.25	4.8
	8SC50-10	5.00	10SCH(HS)	2.38	0.91	1.03	5.450	4.38	5.5
<b>9SC</b>	9SC35	3.50	9SCH(HS)	1.69	1.03	0.06	6.350	3.63	4.1
	9SC44	4.38	9SCH(HS)	2.06	1.03	0.44	6.350	3.63	5.9
	9SC450	5.00	9SCH(HS)	2.38	1.03	0.75	6.350	3.63	6.4
	9SC50-11	5.00	11SCH(HS)	2.38	1.03	0.75	6.350	5.25	7.0
	9SC70-11	7.00	11SCH(HS)	2.38	1.03	1.75	6.350	5.25	10.9
	9SC78-11	7.75	11SCH(HS)	3.75	1.03	2.13	6.350	5.25	12.3
<b>10SC</b>	10SC48	4.75	10SCH(HS)	2.25	1.22	0.34	7.500	4.38	9.8
	10SC50	5.00	10SCH(HS)	2.38	1.22	0.47	7.500	4.38	10.2
	10SC70-13	7.00	13SCH(HS)	3.38	1.22	1.47	7.500	6.13	14.5
	10SC78-13	7.75	13SCH(HS)	3.75	1.22	1.84	7.500	6.13	16.5
	10SC100-13	10.00	13SCH(HS)	4.88	1.22	2.97	7.500	6.13	22.5
<b>11SC</b>	11SC48	4.75	11SCH(HS)	1.50	1.50	0.03	8.625	5.25	12.5
	11SC50	5.00	11SCH(HS)	1.56	1.50	0.06	8.625	5.25	12.6
	11SC70-14	7.00	14SCH	2.56	1.50	1.06	8.625	6.50	16.3
	11SC78-14	7.75	14SCH	2.94	1.50	1.44	8.625	6.50	18.4
	11SC100-14	10.00	14SCH	4.06	1.50	2.56	8.625	6.50	24.6
<b>12SC</b>	12SC70	7.00	12SCH(HS)	2.47	1.69	0.66	10.000	5.75	23.4
	12SC70-14	7.00	14SCH	2.47	1.69	0.66	10.000	6.50	21.3
	12SC78	7.75	12SCH(HS)	2.84	1.69	1.03	10.000	5.75	25.3
	12SC78-14	7.75	14SCH	2.84	1.69	1.03	10.000	6.50	23.4
	12SC100-14	10.00	14SCH	3.97	1.69	2.16	10.000	6.50	29.6
<b>13SC</b>	13SC78	7.75	13SCH(HS)	3.25	1.97	0.56	11.750	6.13	38.4
<b>14SC</b>	14SC78	7.75	14SCH	2.72	2.25	0.03	13.875	6.50	55.2

Notes: ■ 1 indicates: Flanges can be mixed to form different shaft separations.  
■ Metric Flanges and hubs are also available. Consult Lovejoy Engineering for specific information.  
■ See page SF-13 for Performance Data.

SFE



#### SC Type (Spacer) Hub Dimensional Data

Size	Hub Number <sup>1</sup>	ID1 - ID2	L in	SL in	OD in	T in	Number & Size of Cap Screws Req		Weight Hub lbs
		Max Bore Standard Keyway					Qty	Size	
<b>5SC</b>	5SCH	1.125	1.09	0.54	2.00	5/16 - 18	4	#10 - 1-1/2	0.8
<b>6SC</b>	6SCH	1.375	1.22	0.61	2.50	5/16 - 18	4	1/4 - 1-3/4	1.4
<b>7SC</b>	7SCH	1.625	1.47	0.71	2.81	5/16 - 18	4	1/4 - 1-7/8	2.0
<b>8SC</b>	8SCH	1.875	1.72	0.66	3.25	3/8 - 16	4	5/16 - 2-1/4	3.2
	10SCH	2.375	2.34	0.63	4.38	1/2 - 13	4	7/16 - 3-1/4	7.4
	10SCHS	1.625	1.66	0.63	4.38	1/2 - 13	4	7/16 - 2-1/2	5.5
<b>9SC</b>	9SCH	2.125	1.97	1.17	3.63	3/8 - 16	4	3/8 - 2-3/4	4.2
	9SCHS	1.500	1.53	0.63	3.63	3/8 - 16	4	5/8 - 4-1/2	3.7
	11SCH	2.875	2.72	1.36	5.25	1/2 - 13	4	1/2 - 3-1/2	12.2
	11SCHS	1.875	1.91	0.75	5.25	1/2 - 13	4	1/2 - 2-3/4	9.3
<b>10SC</b>	10SCH	2.375	2.34	1.17	4.38	1/2 - 13	4	7/16 - 3-1/4	7.4
	10SCHS	1.625	1.66	0.63	4.38	1/2 - 13	4	7/16 - 2-1/2	5.5
	13SCH	3.375	3.34	1.65	6.13	3/4 - 10	4	5/8 - 4-3/4	19.9
	13SCHS	2.500	2.47	1.24	6.13	3/4 - 10	4	5/8 - 3-1/2	16.0
<b>11SC</b>	11SCH	2.875	2.72	1.36	5.25	1/2 - 13	4	1/2 - 3-1/2	12.2
	11SCHS	1.875	1.91	0.75	5.25	1/2 - 13	4	1/2 - 2-3/4	9.3
	14SCH	3.875	3.84	1.92	6.50	3/4 - 10	4	5/8 - 5	24.2
<b>12SC</b>	12SCH	2.875	2.97	1.44	5.75	5/8 - 11	4	5/8 - 4	16.6
	12SCHS	2.500	2.53	1.12	5.75	5/8 - 11	4	5/8 - 3-1/2	14.1
	14SCH	3.875	3.84	1.92	6.50	3/4 - 10	4	5/8 - 5	24.2
<b>13SC</b>	13SCH	3.375	3.34	1.65	6.13	3/4 - 10	4	5/8 - 4-3/4	19.9
	13SCHS	2.500	2.47	1.24	6.13	3/4 - 10	4	5/8 - 3-1/2	16.0
<b>14SC</b>	14SCH	3.875	3.84	1.92	6.50	3/4 - 10	4	5/8 - 5	24.2


Notes: ■ 1 indicates: SCH = Standard length SCHS = Short length.

■ See page SF-13 for Performance Data.

## SC Type Hub Dimensional Data

### SC Type (Spacer)

- SC (Spacer) Type couplings are available with the most popular shaft separation distances
- Non standard shaft separations can be achieved by combining different spacer flanges
- The "Standard" column illustrates separations available using identical lengths
- The "Combination" column illustrates combined flanges of different separations
- The "Semi-Spacer" column illustrates combinations of SC (Spacer) flanges and standard S flanges



### Type SC (Spacer) Dimensional Data

#### Standard

Spacing	Use Flanges
3-1/2	(2)-SC35
4-3/8	(2)-SC44
5	(2)-SC50
7	(2)-SC70
7-3/4	(2)-SC78
10	(2)-SC100

#### Combination

Spacing	Use Flanges <sup>1</sup>
3-15/16	SC35 & SC44
4-1/4	SC35 & SC50
5-1/4	SC35 & SC70
5-5/8	SC35 & SC78
5-11/16	SC44 & SC70
6	SC50 & SC70
6-1/16	SC44 & SC78
6-7/16	SC50 & SC78
6-3/4	SC35 & SC100 <sup>2</sup>
7-3/16	SC44 & SC100 <sup>2</sup>
7-7/16	SC70 & SC78
7-1/2	SC50 & SC100
8-1/2	SC70 & SC100
8-15/16	SC78 & SC100

#### Semi-Spacer

Spacing	Use Flanges <sup>1</sup>
1-7/8	S & SC35
2-5/16	S & SC44
2-5/8	S & SC50
3-5/8	S & SC70
4	S & SC78
5-1/8	S & SC100

Notes:

- 1 indicates: Check for flange availability of coupling size.
- 2 indicates: Non stock.
- See page SF-13 for Performance Data.

**Sleeve and Flexible Element Chemical Resistance Chart**

Legend: A = Fluid has little or no effect; B = Fluid has minor to moderate effect; C = Fluid has severe effect; - = No data available.

Resistance to:	NBR ("SOX")	Urethane	Hytrell™	EPDM	Neoprene
Acetone	C	C	B	A	B
Ammonia Anhydrous	-	-	-	A	A
Ammonium Hydroxide Solutions	C	C	A	A	A (158°F)
ASTM oil No. 1	A	A	A	C	A
ASTM oil No. 3	A	B	A	C	B-C (158°F)
ASTM reference fuel A	A	A	A	C	B
ASTM reference fuel B	A	B	A	C	C
ASTM reference fuel C	B	C	B	C	C
Benzene	C	C	B	C	C
Butane	A	A	A	C	A
Carbon Tetrachloride	C	C	C	C	C
Chlorobenzene	C	C	C	C	C
Chloroform	C	C	C	C	C
Chromic Acid 10-50%	C	C	-	C	C
Dowtherm A or E solvent	-	-	-	C	C
Ethyl Alcohol	C	C	A	A	A (158°F)
Ethylene Glyco	A	B	A	A	A (158°F)
Fuel Oil	A	C	-	C	A
Gasoline	A	B	A	C	B
Glycerine	A	C	A	A	A
Hydraulic Oils (Petroleum Based)	A	A	A	C	A-B
Hydrochloric Acid, 37% (cold)	C	C	C	A	A-B
Hydrogen Peroxide, 90%	C	-	-	C	C
Isopropyl Alcohol	B	C	A	A	A-B
Kerosene	A	B	A	C	B-C
Lacquer Solvents (MEK)	C	C	C	C	C
Lubricating Oils	B	-	A	C	B
Methyl Alcohol	C	C	A	A	A
Mineral Oil	A	A	A	C	B
Naphtha	C	C	A	C	C
Nitric Acid, 10%	C	C	B	B	B
Nitrobenzene	C	C	C	C	C
Phenol	C	C	B	C	C
Phosphoric Acid, 20%	C	A	-	A	B
Phosphate Esters	-	-	A	C	C
Pickling Solution (20% Nitric Acid, 4% HP)	C	C	C	C	C
Soap Solutions	A	A	A	A	A (158°F)
Sodium Hydroxide, 20%	B	B	A	A	B
Stearic Acid	B	A	A	B	B (158°F)
Sulfuric Acid, up to 50%	C	C	A	B	A-B (158°F)
Sulfuric Acid, 50% to 80%	C	C	C	B	B-C
Tannic Acid, 10%	A	-	A	A	A-B
Toluene	C	C	A	C	C
Trichloroethylene	C	C	B	C	C
Turpentine	A	C	-	C	C
Water	A	-	B (158°F)	A (158°F)	A (212°F)
Xylene	C	C	B	C	C