

| General            |                      |
|--------------------|----------------------|
| COUPLING TYPE      | Elastomeric          |
| COUPLING STYLE     | Split-Tire           |
| COUPLING SIZE      | 20                   |
| SHAFT SPACING      | Close Coupled Spacer |
| COUPLING COMPONENT | Hub                  |
| SHAFT ATTACHMENT   | Bored To Size        |

| Sealing & Lubrication |      |
|-----------------------|------|
| LUBRICATION TYPE      | None |

| Technical             |           |
|-----------------------|-----------|
| RATED TORQUE          | 2308      |
| HP/100                | 3.66 hp   |
| ANGULAR MISALIGNMENT  | 3 lbf     |
| PARALLEL MISALIGNMENT | 0.1875 in |
| AXIAL MISALIGNMENT    | 0.3125 in |

| Dimensions              |           |
|-------------------------|-----------|
| BORE DIAMETER           | 2.375 in  |
| BORE FIT                | Clearance |
| BORE TOLERANCE STANDARD | AGMA 9002 |
| BORE LENGTH             | 2.06 in   |
| OUTSIDE DIAMETER        | 4.48 in   |

| Additional Information     |          |
|----------------------------|----------|
| MAXIMUM SPEED              | 6600 rpm |
| TEMPERATURE RATING MAXIMUM | 220 F    |
| TEMPERATURE RATING MINIMUM | -45 F    |