

Power-Wedge® Cog-Band® Banded Belt

Power-Wedge® Cog-Band® Part Numbers

Part Number Example: **R5VX1000-3** =

R
Banded Construction
5V
Cross Section
X
Cogged Construction
1000
Inside Circumference (inches in tenths: 100.0)
- 3
Number of Ribs

Part Number	Outside Circumference (inches) per rib	Outside Circumference (mm) per rib	Weight (lbs.) per rib
R3VX – Banded 3VX Section Recommended Pulleys: Hi-Cap Wedge – OD, Taper Bushed, or MST (3V)			
R3VX250	26.1	26	0.13
R3VX265	27.6	701	0.14
R3VX280	29.1	739	0.15
R3VX300	31.1	790	0.16
R3VX315	32.6	828	0.16
R3VX335	34.6	879	0.17
R3VX355	36.6	930	0.18
R3VX375	38.6	980	0.19
R3VX400	40.8	1036	0.20
R3VX415	42.3	1074	0.20
R3VX425	43.3	1100	0.21
R3VX440	44.8	1138	0.21
R3VX450	45.8	1163	0.22
R3VX465	47.3	1201	0.23
R3VX475	48.3	1227	0.24
R3VX485	49.3	1252	0.24
R3VX500	50.8	1290	0.25
R3VX530	53.8	1367	0.26
R3VX560	56.8	1443	0.28
R3VX600	60.8	1544	0.30
R3VX630	63.8	1621	0.32
R3VX670	67.8	1722	0.34
R3VX710	71.8	1824	0.36
R3VX750	75.8	1925	0.38
R3VX770	77.8	1976	0.39
R3VX800	80.8	2052	0.40
R3VX820	82.8	2103	0.41
R3VX830	83.8	2129	0.42
R3VX850	85.8	2179	0.43
R3VX900	90.8	2306	0.45
R3VX950	95.8	2433	0.48
R3VX1000	100.8	2560	0.51
R3VX1060	106.8	2713	0.54
R3VX1120	112.8	2865	0.57
R3VX1180	118.8	3018	0.60

Part Number	Outside Circumference (inches) per rib	Outside Circumference (mm) per rib	Weight (lbs.) per rib
R3VX – Banded 3VX Section Recommended Pulleys: Hi-Cap Wedge – OD, Taper Bushed, or MST (3V)			
R3VX1250	125.8	3195	0.63
R3VX1320	132.8	3373	0.67
R3VX1400	140.8	3576	0.71
R5VX – Banded 5VX Section Recommended Pulleys: Hi-Cap Wedge – OD, Taper Bushed, or MST (5V)			
R5VX500	50.8	1290	0.63
R5VX530	53.8	1367	0.66
R5VX560	56.8	1443	0.70
R5VX600	60.8	1544	0.76
R5VX630	63.8	1621	0.80
R5VX670	67.8	1722	0.85
R5VX710	71.8	1824	0.90
R5VX750	75.8	1925	0.95
R5VX800	80.8	2052	1.02
R5VX850	85.8	2179	1.08
R5VX900	90.8	2306	1.15
R5VX950	95.8	2433	1.22
R5VX1000	100.8	2560	1.28
R5VX1030	104.1	2644	1.30
R5VX1060	106.8	2713	1.36
R5VX1120	112.8	2865	1.44
R5VX1180	118.8	3018	1.52
R5VX1200	121.1	3076	1.58
R5VX1250	125.8	3195	1.61
R5VX1320	132.8	3373	1.70
R5VX1400	140.8	3576	1.80
R5VX1460	147.1	3736	1.90
R5VX1500	150.8	3830	1.94
R5VX1600	160.8	4084	2.07
R5VX1700	170.8	4338	2.20
R5VX1800	180.8	4592	2.33
R5VX1900	190.8	4846	2.46
R5VX2000	200.8	5100	2.59

For complete part number, add a hyphen followed by the number of ribs required as indicated in example above.